

CAMSO SKS 532



SKID STEER
LOADERS



Gumiabroncs élettartam



Defektellenálló képesség




Vontatási képesség



ROAD
FREE
COMPANY

CAMSO SKS 532



ENHANCED TREAD DEPTH WITH CURVED LUG DESIGN

- Ensures great durability and improved traction

STEPPED TREAD DESIGN

- Enhances cleanout for improved off-road traction

IMPACT GUARD WITH ENHANCED RIM PROTECTION

- Provides maximum sidewall and rim flange protection, reducing impact damage and flat tires

VOID GUARD

- Enhances tread impact protection to reduce risk of punctures

TIRE SIZE	PR	RIM SIZE	ACTUAL TIRE DIMENSIONS					MAXIMUM INFLATION PRESSURE [PSI]	MAXIMUM TIRE LOAD [lb]			
			O.D. [in]	O.W. [in]	O.T.D. [32 nd]	SLR [in]	RC [in]		Static	5 mph	10 mph	20 mph
5.70 - 12 NHS	4	5JAx12; 4.50-I-70; 4.50-I-90	22.3	6.1	16	10.6	67.3	60	2290	1450	1145	985
23 X 8.50 - 12 SS	6	7JAx12; 7.00-I-70; 7.00-I-90	22.6	8.6	16	10.5	68.3	50	2860	1810	1430	1230
23 X 8.50 - 12 SS	12	7.00-I-70; 7.00-I-90; 7JA	22.5	8.6	16	10.5	67.9	100	4360	2760	2180	1875
26 X 12.00 - 12 SS	10	10.5x12; 10.50-I-70; 10.50-I-90; 8.50-I-70; 8.50-I-90; 8 1/2JA	25.5	12.0	25	11.7	76.9	65	5575	3530	2790	2400
27 X 8.50 - 15 NHS	8	7JAx15	26.7	8.7	18	12.4	80.9	60	4825	2875	2400	2040
31 X 15.50 - 15 NHS	8	13LBx15	31.0	15.6	29	14.4	93.6	45	7315	4360	3645	3090
10-16.5 NHS	10	8.25	30.2	10.9	23	14.0	91.2	75	7440	4710	3720	3205
12-16.5 NHS	12	9.75	32.7	13.0	24	15.1	98.9	80	9985	6320	4995	4300
12-16.5 NHS	14	9.75	32.7	13.1	24	15.0	101.0	90	10710	6780	5355	4610
14-17.5 NHS	14	10.50	36.4	13.8	30	16.7	109.8	80	13495	8540	6745	5805