

SOLIDEAL RES 660 XTREME SERIES

BY CAMSO



RESILIENT



Használati intenzitás



Energia megtakarítás



Gumiabroncs élettartam



Komfort



RESILIENT TIRES

SOLIDEAL RES 660 XTREME SERIES

BY CAMSO

TIRE SIZE	RIM SIZE ⁽¹⁾	HEEL	
		NORMAL	QUICK
5.00-8	3.00D-8	■	■
15x4 1/2-8 (125/75-8)	3.00D-8	■	■
16x6-8 (150/75-8)	4.33R-8	■	■
18x7-8 (180/70-8)	4.33R-8	■	■
140/55-9	4.00E-9		■
6.00-9	4.00E-9	■	■
21x8-9	6.00E-9	■	■
180/60-10	5.00F-10		■
200/50-10	6.50F-10	■	■
6.50-10	5.00F-10	■	■
23x9-10 (225/75-10)	6.50F-10	■	■
23x10-12 (250/60-12)	8.00G-12	■	■
23x12-12 (315/45-12)	10.00G-12	■	■
27x10-12 (250/75-12)	8.00G-12	■	■
7.00-12	5.00S-12	■	■
28x9-15 (8.15-15 & 225/75-15)	7.00-15	■	■
355/45-15 (28x12.5-15)	9.75-15	■	■
355/50-15	9.75-15	■	■
355/65-15 (32x12.1-15)	9.75-15	■	■
250-15 (250/70-15)	7.00-15	■	■
250-15 (250/70-15)	7.50-15	■	■
300-15 (315/70-15)	8.00-15	■	■
7.00-15	5.50-15	■	■
7.00-15	6.00-15	■	
7.50-15	5.50-15	■	■
7.50-15	6.00-15	■	■
7.50-15	6.50-15	■	■
8.25-15	5.50-15	■	■
8.25-15	6.50-15	■	■
400/60-15	11.00 - 15	■	■

TIRE SIZE	RIM SIZE ⁽¹⁾	HEEL	
		NORMAL	QUICK
7.50 - 16	6.00-16	■	
355 / 50 - 20	10.00-20	■	■
9.00 - 20	7.00-20	■	
10.00 - 20	7.00-20	■	
10.00 - 20	7.50-20	■	■
10.00 - 20	8.00-20	■	
12.00 - 20	8.00-20	■	
12.00 - 20	8.50-20	■	
12.00 - 20	10.00-20	■	
12.00 - 20 EW	10.00-20	■	
465 / 55 - 20	16.00-20	■	
12.00 - 24	8.50-24	■	