

FL700

TECHNICAL DATA

TYRE SIZE	PR	TT / TL	RIM		Unloaded Inflated Dimension		SLR	RC	Load Capacity Free Rolling Wheel				Load Capacity Drive Rolling Wheel				Inflation Pressure	
									25 mph (40km/h)		30 mph (50km/h)		25 mph (40km/h)		30 mph (50km/h)			
			Rec. inch	Alt. inch	± 2 % mm	± 2 % mm	mm	± 2.5 % mm	A8 Load Index	MAX. LOAD kgs	B Load Index	MAX. LOAD kgs	A8 Load Index	MAX. LOAD kgs	B Load Index	MAX. LOAD kgs	PSI	Bar
15.5																		
400/60-15.5	18	TL	AG 13.00		400	875	380	2564	149	3875	145	3250	137		133		90	6.2
22.5																		
500/45-22.5	16	TL	AG 16.00		500	1043.9	457	3098.8	154	3750	150	3350	142	2650	138	2360	52	3.5
500/50-22.5	16	TL	AG 16.00		500	1069.3	483	3200.4	158	4250	155	3875	146	3000	142	2650	44	3.0
500/60-22.5	16	TL	AG 16.00	15.00,17.00	500	1170.9	483	3200.4	163	4875	159	4375	151	3450	148	3150	46	3.1
550/45-22.5	16	TL	AG 16.00		551	1069.3	483	3200.4	159	4375	152	3550	147	3075	139	2430	41	2.8
550/60-22.5	16	TL	AG 16.00		551	1239.5	533	3733.8	160	4500	156	4000	148	3150	144	2800	41	2.8
600/50-22.5	16	TL	AG 20.00		599	1170.9	508	3505.2	165	5150	161	4625	153	3650	149	3250	38	2.6
600/50-22.5	18	TL	AG 20.00		599	1170.9	508	3505.2	167	5450	163	4875	155	3875	151	3450	42	2.8
600/55-22.5	16	TL	AG 20.00		599	1229.4	533	3708.4	169	5800	166	5300	156	4000	153	3650	38	2.6
700/40-22.5	16	TL	AG 24.00		701	1170.9	508	3530.6	166	5300	162	4750	154	3750	150	3350	32	2.2
700/50-22.5	16	TL	AG 24.00		701	1270	559	3784.6	174	6700	170	6000	162	4750	158	4250	35	2.4

