

## RIB 3

### IMPLEMENT TIRE

#### TECHNICAL DATA

|      | TYRE SIZE    | PR | TT / TL | RIM       |           | Unloaded Inflated Dimension |          | SLR | RC         | Speed Radius Index | LOAD CAPACITY FREE ROLLING WHEEL |            |           |                       |       |           | Inflation Pressure |     |     |  |
|------|--------------|----|---------|-----------|-----------|-----------------------------|----------|-----|------------|--------------------|----------------------------------|------------|-----------|-----------------------|-------|-----------|--------------------|-----|-----|--|
|      |              |    |         |           |           | SW                          | OD       |     |            |                    | 30 kmph (20 mph) HL V            |            |           | 40 kmph ( 25MPH) HL V |       |           |                    |     |     |  |
|      |              |    |         |           |           |                             |          |     |            |                    | Speed index                      | Load Index | MAX. LOAD | Speed                 | Load  | MAX. LOAD |                    |     |     |  |
|      |              |    |         | Rec. inch | Alt. inch | ± 2 % mm                    | ± 2 % mm | mm  | ± 2.5 % mm |                    | mm                               | Index      | Index     | kgs                   | Index | Index     | kgs                | PSI | Bar |  |
|      |              |    |         |           |           |                             |          |     |            |                    |                                  |            |           |                       |       |           |                    |     |     |  |
| 12.0 |              |    |         |           |           |                             |          |     |            |                    |                                  |            |           |                       |       |           |                    |     |     |  |
|      | 10.0/80-12   | 10 | TL      | 9.0       | 7.0       | 264                         | 710      | 313 | 2080       |                    | A6                               | 126        | 1700      | A8                    | 121   | 1450.0    | 80                 | 5.4 |     |  |
| 15.3 |              |    |         |           |           |                             |          |     |            |                    |                                  |            |           |                       |       |           |                    |     |     |  |
|      | 10.0/75-15.3 | 10 | TL      | 9.0       |           | 274                         | 760      | 356 | 2235       | 360                | A6                               | 128        | 1800      | A8                    | 123   | 1550      | 75                 | 5.2 |     |  |
|      | 10.0/75-15.3 | 14 | TL      | 9.0       |           | 274                         | 760      | 343 | 2235       | 360                | A6                               | 136        | 2240      | A8                    | 130   | 1900      | 103                | 7.1 |     |  |
|      | 11.5/80-15.3 | 10 | TL      | 9.0       |           | 297                         | 845      | 343 | 2227       | 410                | A6                               | 137        | 2300      | A 8                   | 131   | 1950      | 67                 | 4.6 |     |  |
|      | 11.5/80-15.3 | 12 | TL      | 9.0       |           | 297                         | 845      | 343 | 2227       | 410                | A6                               | 141        | 2575      | A 8                   | 135   | 2180      | 81                 | 5.6 |     |  |
|      | 11.5/80-15.3 | 14 | TL      | 9.0       |           | 297                         | 845      | 343 | 2227       | 410                | A6                               | 145        | 2900      | A 8                   | 139   | 2430      | 94                 | 6.5 |     |  |
|      | 11.5/80-15.3 | 18 | TL      | 9.0       |           | 297                         | 845      | 343 | 2227       | 410                | A6                               | 149        | 3250      | A 8                   | 145   | 2900      | 103                | 7.1 |     |  |
|      | 12.5/80-15.3 | 14 | TL      | 9.0       |           | 312                         | 889      | 387 | 2591       | 425                | A6                               | 147        | 3075      | A8                    | 142   | 2650      | 84                 | 5.8 |     |  |
|      | 12.5/80-15.3 | 16 | TL      | 9.0       |           | 312                         | 889      | 387 | 2591       | 425                | A6                               | 150        | 3350      | A8                    | 146   | 3000      | 94                 | 6.5 |     |  |
| 18.0 |              |    |         |           |           |                             |          |     |            |                    |                                  |            |           |                       |       |           |                    |     |     |  |
|      | 12.5/80-18   | 12 | TL      | W9        | 11.0      | 307                         | 965      | 432 | 2819       | 475                | A6                               | 148        | 3150      | A8                    | 142   | 2650      | 73                 | 5.0 |     |  |
|      | 12.5/80-18   | 16 | TL      | W9        | 11.0      | 307                         | 965      | 432 | 2819       | 475                | A6                               | 154        | 3750      | A8                    | 150   | 3350      | 97                 | 6.5 |     |  |

