

# GREEN XLR

## 65 SERIES (R1-W)



### TECHNICAL DATA

TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension ± 2%		SLR	RC ± 2.5%	SRI	SPEED	LOAD CAPACITY ( KG / TIRE )												
			Rec.	Alt.	S.W.	O.D.					mm	mm	mm	mm	mm	mm							
																	mm	mm	mm	mm	mm	mm	mm
<b>24.0</b>																							
440/65R24	135 D / 138 A8	TL	W 14 L	W13, W15	441	1182	538	3546	575	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	<b>2.4</b>					
										65	1050	1225	1375	1530	1680	1810	2010	<b>2180</b>					
										50	1100	1285	1445	1605	1765	1905	2110	2290					
										40	1135	1325	1490	1655	1820	1960	2175	2360					
										30	1205	1410	1585	1760	1935	2085	2310	2510					
										10 LT	1405	1640	1845	2050	2255	2430	2695	2925					
										10 HT	1205	1410	1585	1760	1935	2085	2310	2510					
480/65R24	140 D / 143 A8	TL	W 15 L	W14L	479	1234	562	3730	600	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	<b>2.4</b>					
										65	1200	1400	1575	1750	1925	2075	2300	<b>2500</b>					
										50	1260	1470	1655	1840	2025	2180	2415	2625					
										40	1310	1530	1720	1910	2100	2265	2510	2725					
										30	1380	1610	1815	2015	2215	2390	2645	2875					
										10 LT	1610	1880	2115	2345	2580	2785	3085	3350					
										10 HT	1380	1610	1815	2015	2215	2390	2645	2875					
540/65R24	146 D / 149 A8	TL	W 16 L	W18L	530	1312	590	3930	625	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	<b>2.4</b>					
										65	1440	1680	1890	2100	2310	2490	2760	<b>3000</b>					
										50	1515	1765	1985	2205	2430	2615	2900	3150					
										40	1560	1820	2050	2275	2505	2700	2990	3250					
										30	1660	1935	2175	2415	2660	2865	3175	3450					
										10 LT	1930	2255	2535	2815	3100	3340	3700	4020					
										10 HT	1660	1935	2175	2415	2660	2865	3175	3450					
<b>28.0</b>																							
440/65R28	138 D / 141 A8	TL	W 14 L	W13	441	1283	590	3878	625	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	<b>2.4</b>					
										65	1135	1325	1490	1655	1820	1960	2175	<b>2360</b>					
										50	1195	1390	1565	1740	1910	2060	2285	2480					
										40	1240	1445	1625	1805	1985	2140	2370	2575					
										30	1305	1525	1715	1905	2095	2255	2500	2715					
										10 LT	1520	1775	1995	2220	2440	2630	2915	3165					
										10 HT	1305	1525	1715	1905	2095	2255	2500	2715					
480/65R28	142 D / 145 A8	TL	W 15 L	W14L	479	1335	610	4058	650	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	<b>2.4</b>					
										65	1275	1485	1670	1855	2045	2200	2440	<b>2650</b>					
										50	1340	1560	1755	1950	2145	2315	2565	2785					
										40	1395	1625	1830	2030	2235	2410	2670	2900					
										30	1465	1710	1925	2135	2350	2535	2810	3050					
										10 LT	1710	1995	2240	2490	2740	2955	3275	3555					
										10 HT	1465	1710	1925	2135	2350	2535	2810	3050					

# TECHNICAL DATA

TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension ± 2%		SLR	RC ± 2.5%	SRI	SPEED	LOAD CAPACITY ( KG / TIRE )								
					S.W.	O.D.					LOAD CAPACITY ( KG / TIRE )								
											mm	mm	mm	mm	mm	mm	mm	mm	mm
540/65R28	149 D / 152 A8	TL	W 16 L	W 18 L	530	1413	643	4253	675	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	1560	1820	2050	2275	2505	2700	2990	3250
											50	1640	1910	2150	2390	2630	2830	3140	3415
											40	1705	1990	2235	2485	2735	2945	3265	3550
											30	1795	2095	2355	2615	2880	3100	3440	3740
											5LT	2090	2440	2745	3050	3355	3615	4005	4355
1795	2095	2355	2615	2880	3100	3440	3740												
600/65R28	154 D / 157 A8	TL	DW 20 B	W 18 L	611	1491	670	4470	700	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	1800	2100	2365	2625	2890	3115	3450	3750
											50	1890	2205	2480	2755	3030	3270	3625	3940
											40	1980	2310	2600	2890	3175	3425	3795	4125
											30	2070	2415	2715	3020	3320	3580	3970	4315
											5LT	2410	2815	3165	3520	3870	4170	4625	5025
2070	2415	2715	3020	3320	3580	3970	4315												
<b>30.0</b>																			
540/65R30	150 D / 153 A8	TL	W 16 L	W 18 L	530	1460	670	4403	700	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	1610	1875	2110	2345	2580	2780	3080	3350
											50	1690	1970	2215	2460	2710	2920	3235	3520
											40	1750	2045	2300	2555	2810	3030	3360	3650
											30	1850	2155	2425	2695	2965	3200	3545	3855
											5LT	2155	2515	2830	3140	3455	3725	4130	4490
1850	2155	2425	2695	2965	3200	3545	3855												
<b>34.0</b>																			
600/65R34	157 D / 160 A8	TL	D W20B	W18L	611	1644	742	4960	775	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	1980	2310	2600	2890	3180	3425	3795	4125
											50	2085	2430	2735	3035	3340	3600	3990	4335
											40	2160	2520	2835	3150	3465	3735	4140	4500
											30	2280	2660	2990	3325	3655	3940	4370	4745
											10 LT	2655	3100	3485	3875	4260	4590	5090	5530
10 HT	2280	2660	2990	3325	3655	3940	4370	4745											
<b>38.0</b>																			
540/65R38	153 D / 156 A8	TL	W16L	W18L	530	1667	760	5059	800	psi / mph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	1755	2045	2300	2555	2815	3030	3360	3650
											50	1845	2150	2420	2685	2955	3185	3530	3835
											40	1920	2240	2520	2800	3080	3320	3680	4000
											30	2020	2355	2650	2940	3235	3490	3865	4200
											10 LT	2350	2745	3085	3430	3770	4065	4505	4895
10 HT	2020	2355	2650	2940	3235	3490	3865	4200											
600/65R38	159 D / 162 A8	TL	DW 20 B	W 18 L	611	1745	790	5247	825	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	2100	2450	2755	3065	3370	3630	4025	4375
											50	2205	2575	2895	3215	3535	3815	4225	4595
											40	2280	2660	2995	3325	3660	3945	4370	4750
											30	2415	2820	3170	3520	3875	4175	4630	5030
											5LT	2815	3285	3695	4105	4515	4865	5395	5865
2415	2820	3170	3520	3875	4175	4630	5030												
650/65R38	163 D / 166 A8	TL	DW 20 B		645	1811	830	5483	875	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	2340	2730	3070	3415	3755	4045	4485	4875
											50	2455	2865	3225	3585	3940	4250	4710	5120
											40	2545	2970	3340	3710	4080	4400	4875	5300
											30	2690	3140	3530	3925	4315	4655	5160	5605
											5LT	3135	3660	4115	4575	5030	5420	6010	6535
2690	3140	3530	3925	4315	4655	5160	5605												
<b>42.0</b>																			
650/65R42	165 D / 168 A8	TL	DW 20 B		645	1913	864	5740	925	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	
											65	2470	2885	3245	3605	3965	4275	4740	5150
											50	2595	3030	3245	3785	4165	4490	4975	5410
											40	2690	3135	3530	3920	4310	4650	5150	5600
											30	2845	3315	3730	4145	4560	4915	5450	5925
											5LT	3310	3865	4350	4830	5315	5730	6350	6900
2845	3315	3730	4145	4560	4915	5450	5925												