

Longer
run time

Increased
fuel efficiency

High
Load Capacity

Exceptional
ride comfort



70 SERIES (R1-W)

BUILT FOR HEAVY
DUTY RADIAL TRACTORS

Guarantees high comfort levels for the driver owing to its flexible sidewall. It is equipped with a heat dissipating notch- an innovative feature that contributes to a longer run time and increased tire durability, thereby providing the user with extensive tire life with great traction and good soil protection, it is the ideal tire for reduced working time and high cost efficiency. The special inter-lug "mud breakers" prevent mud from sticking to the tire and the self-cleaning tread design channels dirt out of the tire, which maintains the tire weight and improves fuel efficiency. Its round shoulders minimize soil compaction and protects your fields.

GREEN XLR 70 Series is best suited for...

- Better lug stability provided by our New Tie Bar design
- Increased load capacity, ride comfort & protection from weathering
- Increased road ability
- High abrasion resistance

TECHNICAL DATA

TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension $\pm 2\%$		SLR	RC $\pm 2.5\%$	SRI	SPEED	LOAD CAPACITY (KG / TYRE)									
			Rec.	Alt.	S.W. (mm)	O.D. (mm)					(mm)	(mm)	(mm)	(mm)	bar / kmph					
24.0																				
360/70R24	122 A8/ B	TL	W 11	W 10, W12	357	1152	519	3400	550	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6				
										50	825	960	1095	1235	1365	1500				
										40	825	960	1095	1235	1365	1500				
										30	885	1025	1170	1320	1460	1605				
										10LT	1105	1285	1465	1650	1830	2010				
										10HT	885	1025	1170	1320	1460	1605				
380/70R24	125 A8/ B	TL	W 12	W 11, W13	380	1190	538	3560	575	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6				
										50	910	1055	1205	1355	1500	1650				
										40	910	1055	1205	1355	1500	1650				
										30	970	1130	1290	1450	1605	1765				
										10LT	1215	1415	1615	1815	2010	2210				
										10HT	970	1130	1290	1450	1605	1765				
420/70R24	130 A8/ B	TL	W 13	W 12, W14 L	418	1248	554	3680	600	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6				
										50	1045	1215	1385	1562	1730	1900				
										40	1045	1215	1385	1562	1730	1900				
										30	1120	1300	1485	1673	1850	2035				
										10LT	1400	1630	1860	2092	2315	2545				
										10HT	1120	1300	1485	1673	1850	2035				
480/70R24	138 A8/ B	TL	W 15 L	W 14 L, W 16 L	479	1316	580	3894	625	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6				
										50	1230	1510	1725	1940	2150	2360				
										40	1230	1510	1725	1940	2150	2360				
										30	1390	1615	1845	2075	2230	2525				
										10LT	1740	2025	2310	2600	2880	3160				
										10HT	1740	2025	2310	2600	2880	3160				
28.0																				
380/70R28	127 A8/ B	TL	W 12	W 11, W13	380	1293	586	3883	625	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6				
										50	965	1120	1280	1440	1595	1750				
										30	1030	1200	1365	1540	1705	1875				
										10LT	1290	1500	1710	1930	2135	2345				
										10HT	1030	1200	1365	1540	1705	1875				
420/70R28	133 A8/ B	TL	W 13	W 12, W14 L	418	1349	604	4020	650	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6				
										50 / 40	1135	1320	1505	1695	1875	2060				
										30	1210	1410	1610	1815	2005	2205				
										10LT	1515	1765	2015	2270	2510	2760				
										10HT	1210	1410	1610	1815	2005	2205				
480/70R28	140 A8/ B	TL	W 15 L	W 14 L, W 16 L	479	1421	634	4183	675	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6				
										50 / 40	1375	1600	1825	2055	2275	2500				
										40	1375	1600	1825	2055	2275	2500				
										30	1470	1710	1955	2200	2435	2675				
										10LT	1845	2145	2445	2755	3050	3350				
										10HT	1470	1710	1955	2200	2435	2675				

TECHNICAL DATA

TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension \pm 2%		SLR	RC \pm 2.5%	SRI	SPEED	LOAD CAPACITY (KG / TYRE)										
					S.W.	O.D.															
			Rec.	Alt.	(mm)	(mm)	(mm)	(mm)	(mm)		(mm)	(mm)	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6		
30.0																					
420/70R30	134 A8/B	TL	W 13	W 12, W14 L	418	1398	631	4172	675	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	1165	1355	1550	1745	1930	2120					
										40	1165	1355	1550	1745	1930	2120					
										30	1250	1450	1655	1865	2065	2270					
										10LT	1560	1820	2075	2335	2585	2840					
10HT	1250	1450	1655	1865	2065	2270															
480/70R30	141 A8/B	TL	W 15 L	W 14 L, W 16 L	479	1478	659	4322	700	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	1415	1650	1880	2115	2345	2575					
										40	1415	1650	1880	2115	2345	2575					
										30	1515	1765	2010	2265	2505	2755					
										10LT	1900	2210	2520	2835	3140	3450					
10HT	1515	1765	2010	2265	2505	2755															
600/70R30	152 A8/B	TL	DW 20 B	DW18 L, W18L	591	1602	711	4774	750	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	1955	2270	2590	2920	3230	3550					
										40	1955	2270	2590	2920	3230	3550					
										30	2090	2430	2775	3125	3455	3800					
										10LT	2615	3045	3475	3910	4330	4755					
10HT	2090	2430	2775	3125	3455	3800															
34.0																					
480/70R34	149 A8/B	TL	W 15 L	W 14 L, W 16 L	479	1580	711	4759	750	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4			
										50 / 40	1530	1755	2015	2275	2535	2795	3025	3250			
										30	1635	1880	2155	2436	2710	2990	3235	3480			
										10LT	2045	2350	2700	3049	3395	3745	4050	4355			
										10HT	1635	1880	2155	2436	2710	2990	3235	3480			
520/70R34	148 A8/B	TL	W 16 L	W 15 L, W 18 L	516	1640	739	4901	775	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	1735	2015	2300	2590	2865	3150					
										30	1855	2155	2460	2770	3065	3370					
										10LT	2320	2700	3080	3470	3840	4220					
										10HT	1855	2155	2460	2770	3065	3370					
38.0																					
480/70R38	145 A8/B	TL	W 15 L	W 14 L, W 16 L	479	1681	764	5015	800	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	1595	1855	2115	2385	2640	2900					
										30	1705	1985	2265	2550	2825	3105					
										10LT	2135	2485	2835	3195	3535	3885					
										10HT	1705	1985	2265	2550	2825	3105					
520/70R38	150 A8/B	TL	W 16 L	W 15 L, W 18 L	516	1749	793	5300	825	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	1845	2144	2445	2755	3050	3350					
										30	1970	2294	2615	2945	3260	3585					
										10LT	2470	2875	3295	3690	4085	4490					
										10HT	1970	2295	2615	2945	3260	3585					
580/70R38	155 A8/B	TL	W 18 L		577	1827	821	5505	875	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	2130	2480	2830	3185	3525	3875					
										30	2280	2655	3025	3405	3775	4145					
										10LT	2855	3325	3790	4270	4725	5195					
										10HT	2280	2655	3025	3405	3775	4145					
710/70R38	166 A8/B	TL	DW 23 B		716	1959	859	5751	925	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6					
										50 / 40	2915	3390	3870	4355	4825	5300					
										30	3120	3630	4140	4660	5160	5670					
										10LT	3120	3630	4140	4660	5160	5670					
										10HT	3120	3630	4140	4660	5160	5670					
42.0																					
710/70R42	173 A8/B	TL	DW 23 B		716	2061	922	6174	975	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4			
										50 / 40	3055	3510	4030	4550	5070	5590	6045	6500			
										30	3270	3755	4310	4869	5425	5980	6470	6955			
										10LT	3270	3755	4310	4869	5425	5980	6470	6955			
										10HT	3270	3755	4310	4869	5425	5980	6470	6955			



LIMITED WARRANTY

All tires manufactured by Global Rubber Industries (Pvt) Ltd. are covered under limited warranty against materials, workmanship and any other manufacturing defects subjected to the usage of these tires under specified conditions. If any tire covered by this warranty is identified as unserviceable tire due to a material / workmanship /any other manufacturing defect, we will either repair the tire or make an allowance on purchase of new tire as per the current price of a new tire by the percentage of original tread worn off at the time of making the claim.

The cost of transportation, service, and sales tax already paid will be borne by the owner of the claimed tire. This limited warranty is made for the exclusive benefit of the tire owner actually using the product. No other warranty of liability, expressed or implied, is applicable to this limited warranty or to our products.

Business today is complex, ambiguous and uncertain – a little like life itself. To help you advance and attain your goals, you need something that is completely the opposite. GRI tires are robustly engineered and relentlessly tested to give you assured performance, so you can get a grip on things that really matter to you. Whatever your ambition, GRI will get you there.

DISTRIBUTOR

GRI

28, Joseph's Lane, Colombo 4, Sri Lanka
Tel: +94 11 259 8831 Fax: +94 11 255 1091 Email: info@gritires.com