

95 SERIES (R1-W)



TECHNICAL DATA

TYRE SIZE	LOAD INDEX / SPEED INDEX	TYPE	RIM		Unloaded inflated Dimension ± 2%		SLR	RC ± 2.5%	SRI	SPEED	LOAD CAPACITY (KG / TIRE)														
			Rec.	Alt.	S.W. (mm)	O.D. (mm)					LOAD CAPACITY (KG / TIRE)														
											(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
32.0																									
270/95R32 (11.2R32)	136 A8 / B	TL	W 9	W 8, W 10	275	1327	614	4044	625	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4					
										50	875	1145	1390	1525	1615	1770	1930	2085	2240						
										40	875	1145	1390	1525	1615	1770	1930	2085	2240						
										30	935	1225	1485	1630	1730	1895	2065	2230	2395						
										10	1045	1315	1615	1920	2220	2285	2555	2825	3095	3360					
46.0																									
300/95R46 (12.4R46)	148 A8 / B	TL	W 9	W 10, DW 10, W 11	295	1738	812	5318	825	bar / kmph	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4		
										50	1105	1295	1485	1670	1860	2015	2205	2365	2585	2805	2995	3150			
										40	1105	1295	1485	1670	1860	2015	2205	2365	2585	2805	2995	3150			
										30	1180	1385	1590	1790	1990	2160	2360	2530	2765	3005	3205	3375			
										20	1355	1590	1825	2055	2285	2480	2710	2905	3175	3450	3680	3875			
380/90R46 (14.9R46)	155 A8 / B	TL	W 12	W 11, W 13	380	1852	859	5596	875	bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6							
										50	1785	2285	2790	3065	3295	3605	3875								
										40	1785	2285	2790	3065	3295	3605	3875								
										30	1910	2450	2990	3285	3530	3860	4150								
										10	2095	2740	3315	3955	4540	4715	5235	5815							
48.0																									
230/95R48 (9.5R48)	136 A8 / B	TL	W 8	W 7	238	1656	792	5085	800	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4					
										50	875	1145	1390	1525	1615	1770	1930	2085	2240						
										40	875	1145	1390	1525	1615	1770	1930	2085	2240						
										30	935	1225	1485	1630	1730	1895	2065	2230	2395						
										10	1045	1315	1615	1920	2220	2285	2555	2825	3095	3360					
270/95R48 (11.2R48)	144 A8 / B	TL	W 9	W 8, W 10	275	1733	820	5351	825	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4					
										50	1095	1430	1735	1905	2020	2210	2410	2605	2800						
										40	1095	1430	1735	1905	2020	2210	2410	2605	2800						
										30	1170	1530	1860	2040	2160	2365	2580	2785	2995						
										10	1305	1645	2020	2400	2775	2860	3195	3530	3865	4195					
340/85R48 (13.6R48)	152 A8 / B	TL	W 12	W 11	353	1797	855	5572	875	bar / kmph	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4					
										50	1390	1815	2200	2420	2560	2805	3055	3300	3550						
										40	1390	1815	2200	2420	2560	2805	3055	3300	3550						
										30	1485	1940	2355	2585	2740	3000	3270	3535	3800						
										10	1655	2085	2560	3045	3520	3625	4050	4475	4905	5325					