



Technical Data

Tire Size	Rim Size	Clip on									Other Vehicles load capacity (Kg)		Profile
			Max width ±1% (mm)	OD ± 2% (inch)	Max width ±1% (inch)	OD ± 2% (inch)	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 Km/h	10 Km/h	
4.00-8	3.00 D-8	•	106	406	4.17	15.98	2095	1610	950	730	950	860	UT
5.00-8	3.00 D-8	•	120	446	4.72	17.56	3120	2405	1415	1090	1415	1285	UT
5.00-8	3.00 D-8	•	116	446	4.57	17.56	3120	2403	1415	1090	1415	1285	SM
15x4 1/2-8	125/75-8	•	114	377	4.49	14.84	2295	1765	1040	800	1040	945	UT
16x6-8	150/75-8	•	151	411	5.94	16.18	3210	2535	1455	1150	1495	1360	UT
18x7-8	180/70-8	•	153	453	6.02	17.83	4730	3640	2145	1650	2145	1945	UT
140/55-9	4.00 E-9	•	129	375	5.08	14.76	2580	1986	1170	900	1170	1060	UT
6.00-9	4.00 E-9	•	137	519	5.39	20.43	4155	3195	1885	1450	1885	1710	UT
6.00-9	4.00 E-9	•	140	520	5.51	20.47	4156	3197	1885	1450	1885	1710	SM
21x8-9	200/75-9	•	186	518	7.32	20.39	6075	4675	2755	2120	2755	2505	UT
6.50-10	5.00 F-10	•	160	561	6.30	22.09	5160	3970	2340	1800	2340	2125	UT
200/50-10	6.50 F-10	•	195	455	7.68	17.91	5445	4190	2470	1900	2470	2240	UT
23x9-10	225/75-10	•	200	580	7.87	22.83	7595	5840	3445	2650	3445	3125	UT
7.00-12	5.00 S-12	•	171	650	6.73	25.59	6435	4940	2920	2240	2920	2645	UT
23x10-12	8.00 G-12	•	234	578	9.21	22.76	8310	6390	3770	2900	3770	3420	UT
27x10-12	250/75-12	•	239	677	9.41	26.65	8600	6615	3900	3000	3900	3540	UT
7.00-15	5.50-15	•	179	722	7.05	28.43	7815	6005	3545	2725	3545	3215	UT
250-15	250/70-15	•	221	722	8.70	28.43	10470	8045	4750	3650	4750	4300	UT
250-15	250/70-15	•	221	722	8.70	28.43	10470	8045	4750	3650	4750	4300	UT
8.15-15 (28x9-15)	225/75-15	•	217	691	8.54	27.20	8310	6390	3770	2900	3900	3540	UT
8.25-15	6.50-15	•	212	810	8.35	31.89	10470	8045	4750	3650	4750	4300	UT
300-15	315/70-15	•	252	824	9.92	32.44	12895	9920	5850	4500	5850	5310	UT
28x12.5-15	355/45-15	•	292	697	11.50	27.44	12185	9375	5525	4250	5525	5015	UT
355/65-15	9.75-15	•	300	819	11.81	32.24	17190	13230	7800	6000	2000	6430	UT
9.00-20	6.50-20	•	224	974	8.82	38.35	11775	9813	5340	4450	5340	5200	UT
9.00-20	7.00-20	•	224	974	8.82	38.35	11775	9813	5340	4450	5340	5200	UT
10.00-20	7.00-20	•	257	1016	10.10	40.00	13227	11022	6000	5000	6000	5450	UT
10.00-20	7.50-20	•	257	1016	10.10	40.00	13227	11022	6000	5000	6000	5450	UT
10.00-20	8.00-20	•	257	1016	10.10	40.00	13227	11022	6000	5000	6000	5450	UT
12.00-20	8.00-20	•	271	1090	10.68	42.91	16532	13777	7500	6250	7500	6810	UT
12.00-20	8.50-20	•	271	1090	10.68	42.91	16532	13777	7500	6250	7500	6810	UT
12.00-20	10.00-20	•	297	1090	11.70	42.91	17119	14262	7765	6470	7765	7050	UT



GRI
Built To Move