

FLOTATION PRO

Ø	Tyre size	Service description	Nominal inflation pressure (bar)		 mm	 mm	 mm	 mm	Page
22.5	560/45 R 22.5 IMP	146 D	3,2	AG 16.00	545	1085	490	3295	158
	560/45 R 22.5 IMP	152 D	4,0	AG 16.00	545	1085	490	3295	158
	560/60 R 22.5 IMP	155 D	3,2	AG 16.00	565	1250	560	3850	159
	560/60 R 22.5 IMP	161 D	4,0	AG 16.00	565	1250	560	3850	159
	560/60 R 22.5 IMP	165 D	5,0	AG 16.00	565	1250	560	3850	160
	620/40 R 22.5 IMP	148 D	3,2	AG 20.00	610	1080	495	3330	160
	620/40 R 22.5 IMP	154 D	4,0	AG 20.00	610	1080	495	3330	161
	620/50 R 22.5 IMP	154 D	3,2	AG 20.00	610	1185	540	3640	161
	620/50 R 22.5 IMP	161 D	4,0	AG 20.00	610	1185	540	3640	162
	650/50 R 22.5 IMP	157 D	3,2	AG 20.00	645	1250	560	3850	162
	650/50 R 22.5 IMP	163 D	4,0	AG 20.00	645	1250	560	3850	163
	710/40 R 22.5 IMP	155 D	3,2	AG 24.00	705	1140	520	3520	163
	710/40 R 22.5 IMP	161 D	4,0	AG 24.00	705	1140	520	3520	164
26.5	620/55 R 26.5 IMP	166 D	4,0	AG 20.00	625	1360	620	4200	164
	710/50 R 26.5 IMP	170 D	4,0	AG 24.00	710	1360	620	4200	165
	800/45 R 26.5 IMP	174 D	4,0	AG 28.00	800	1370	625	4200	165

For the explanation of the symbols and abbreviations, see the inside of the last page.



FLOTATION^{PRO}

MEETS THE HIGH DEMANDS
OF PROFESSIONALS