

Ø	Tyre size	Service description	Nominal inflation pressure (bar)		 mm	 mm	 mm	 mm	Page
15.3	260/70 - 15.3 IMP	122 A8	3,2	9.00	270	755	345	2280	168
	260/70 - 15.3 IMP	126 A8	3,6	9.00	270	755	345	2280	168
	260/70 - 15.3 IMP	131 A8	5,0	9.00	270	755	345	2280	169
	300/80 - 15.3 IMP	132 A8	2,8	9.00	295	865	385	2575	169
	300/80 - 15.3 IMP	138 A8	3,6	9.00	295	865	385	2575	170
	300/80 - 15.3 IMP	141 A8	4,0	9.00	295	865	385	2575	170
15.5	400/60 - 15.5 IMP	145 A8	3,6	AG 13.00	410	850	380	2530	171
16	340/55 - 16 IMP	133 A8	3,2	11	345	780	365	2360	171
17	380/55 - 17 IMP	133 A8	2,4	13.00	380	845	385	2530	172
	380/55 - 17 IMP	138 A8	2,8	13.00	380	845	385	2530	172
	480/45 - 17 IMP	140 A8	2,4	16.00	480	860	400	2565	173
	480/45 - 17 IMP	146 A8	3,2	16.00	480	860	400	2565	173
	500/50 - 17 IMP	140 A8	2,0	16.00	500	950	430	2890	174
	500/50 - 17 IMP	149 A8	2,8	16.00	500	950	430	2890	174
20	400/70 - 20 IMP	150 A8	2,8	14	420	1080	485	3215	175
	460/65 - 20 IMP	155 A8	2,8	14	460	1100	485	3300	175
	500/55 - 20 IMP	150 A8	2,4	16.00	515	1060	475	3160	176
22.5	560/60 - 22.5 IMP	167 A8	2,8	AG 16.00	565	1240	550	3700	176
	600/55 - 22.5 IMP	168 A8	2,8	AG 20.00	625	1230	550	3700	177
	710/45 - 22.5 IMP	171 A8	2,8	AG 24.00	730	1240	550	3700	177



FLOTATION+

IDEAL FOR HEAVY DUTY WORK