

TRAXION+ 65-SERIES

Ø	Tyre size	Service description	Nominal inflation pressure (bar)		 mm	 mm	 mm	 mm	Page	
16	320/65 R 16	117 D	2,4	W10	320*	825*	380*	2475*	34	N
18	320/65 R 18	119 D	2,4	W9	310*	875*	405*	2630*	34	N
	340/65 R 18	122 D	2,4	W9	325*	907*	420*	2730*	35	N
20	420/65 R 20	135 D	2,4	W13	420*	1055*	490*	3165*	35	N
24	440/65 R 24	128 D	1,6	DW14L	440	1185	570	3600	36	
	480/65 R 24	133 D	1,6	DW15L	490	1250	610	3760	36	
	540/65 R 24	140 D	1,6	DW16L	540	1315	620	3960	37	
28	440/65 R 28	131 D	1,6	DW14L	440	1285	615	3890	37	
	480/65 R 28	136 D	1,6	DW15L	490	1350	625	4020	38	
	540/65 R 28	142 D	1,6	DW16L	540	1410	660	4240	38	
30	540/65 R 30	143 D	1,6	DW16L	540	1460	670	4400	39	
	540/65 R 30	150 D	2,4	DW16L	540	1460	670	4400	39	
34	540/65 R 34	145 D	1,6	DW16L	540	1580	745	4755	40	
	540/65 R 34	152 D	2,4	DW16L	540	1580	745	4755	40	
	600/65 R 34	151 D	1,6	DW18L	610	1640	770	4930	41	
38	540/65 R 38	147 D	1,6	DW16L	540	1685	780	5080	41	
	600/65 R 38	153 D	1,6	DW18L	610	1750	810	5210	42	
	650/65 R 38	157 D	1,6	DW20B	660	1835	840	5450	42	
42	650/65 R 42	158 D	1,6	DW20B	660	1935	890	5775	43	



TRAXION +

HIGHEST PRODUCTIVITY FOR MODERN
HIGH-TECH TRACTORS