

Ø	Tyre size	Service description	Nominal inflation pressure (bar)		 mm	 mm	 mm	 mm	Page
24	280/85 R 24	115 A8/B	1,6	W10	295	1090	520	3275	62
	280/85 R 24	130 A8/B	4,0	W10	295*	1095*	520*	3275*	62
	320/85 R 24	122 A8/B	1,6	W11	335	1145	540	3430	63
	340/85 R 24	125 A8/B	1,6	W12	360	1190	550	3535	63
	380/85 R 24	131 A8/B	1,6	W13	400	1240	580	3710	64
	420/85 R 24	137 A8/B	1,6	DW15L	450	1320	620	3925	64
28	280/85 R 28	118 A8/B	1,6	W10	285	1195	545	3570	65
	320/85 R 28	124 A8/B	1,6	W11	335	1250	585	3725	65
	340/85 R 28	127 A8/B	1,6	W12	360	1290	610	3870	66
	380/85 R 28	133 A8/B	1,6	W13	400	1345	630	3985	66
	420/85 R 28	139 A8/B	1,6	DW15L	455	1415	660	4215	67
30	380/85 R 30	135 A8/B	1,6	W12	390	1410	645	4150	67
	420/85 R 30	140 A8/B	1,6	DW15L	455	1470	685	4425	68
	460/85 R 30	145 A8/B	1,6	DW15L	490	1545	725	4605	68
34	380/85 R 34	137 A8/B	1,6	W12	390	1505	680	4470	69
	420/85 R 34	142 A8/B	1,6	DW15L	455	1570	735	4700	69
	460/85 R 34	147 A8/B	1,6	DW16L	490	1640	765	4915	70
38	340/85 R 38	133 A8/B	1,6	W12	360	1550	730	4680	70
	380/80 R 38	142 A8/B	2,4	W12	390	1580	735	4820	71
	420/85 R 38	144 A8/B	1,6	DW15L	455	1670	780	5035	71
	460/85 R 38	149 A8/B	1,6	DW16L	490	1750	815	5205	72
	520/85 R 38	155 A8/B	1,6	DW18L	555	1830	850	5465	72
42	480/80 R 42	156 A8/B	2,4	DW16L	500	1850	855	5600	73
	520/85 R 42	157 A8/B	1,6	DW18L	555	1930	905	5785	73
46	480/80 R 46	158 A8/B	2,4	DW16L	500	1950	900	5885	74
	520/85 R 46	158 A8/B	1,6	DW16L	535	2050	930	6150	74
50	480/80 R 50	159 A8/B	2,4	DW16L	500	2045	950	6225	75

N

