




V64/V64+



THE STANDARD FOR
EFFICIENT HAY MAKING

Profil	Tyre size	PR	Service description	Nominal inflation pressure (bar)		 mm	 mm	Page
V50	5.00 - 8	10	66 A6	6,00	3.00D	130	455	200
V50	6.00 - 9	10	94 A6	5,00	4.00E	165	540	200
V60	3.00 - 4	4	30 A6	3,50	2.10	90	275	200
V60	4.00 - 4	4	43 A6	2,75	2.10	100	315	200
V60	3.50 - 6	4	45 A6	3,00	2.50A	100	355	200
V60	3.50 - 8	4	52 A6	3,00	2.50A	100	395	201
V60	4.00 - 8	4	57 A6	2,75	2.50A	105	425	201
V61	15x 6.00 - 6	4	61 A6	2,50	4.50A	160	380	201
V61	170/60 - 8	6	71 A6	3,00	5.50A	170	425	201
V61	18x 8.50 - 8	4	77 A6	2,00	7.00I	210	465	201
V61	18x 8.50 - 8	6	85 A6	3,00	7.00I	210	465	202
V64	3.50 - 6	4	45 A6	3,00	2.50A	100	355	202
V64+	160/65 - 6		60 A8	2,40	4.50A	160	365	202
V64+	160/65 - 6		66 A8	3,20	4.50A	160	365	202
V64	3.50 - 8	4	52 A6	3,00	2.50A	100	395	202
V64+	170/60 - 8		65 A8	2,40	5.50A	170	410	203
V64+	170/60 - 8		71 A8	3,20	5.50A	170	410	203
V64+	210/60 - 8		83 A8	3,20	7.00I	215	455	203
V67	3.00 - 4	4	30 A6	3,50	2.10	90	275	203
V67	4.00 - 4	4	43 A6	5,00	2.10	100	315	203
V67	3.50 - 6	4	45 A6	3,00	2.50A	100	355	204
V67	3.50 - 8	4	52 A6	3,00	2.50A	100	395	204
V67	4.00 - 8	4	57 A6	2,75	2.50A	105	425	204
V67	4.00 - 12	4	66 A6	2,75	3.00D	110	515	204

